



PROTECTING, PRESERVING, AND PERFORMING SINCE 1932

# **TECHNICAL BULLETIN**

## **Technical Service Bulletin**

### **Golden Touch® Fast Flush #1698 REVISED APPLICATION PROCEDURE**

**Date: November 1, 2015**

**For Professional Use Only. Directions:** Use Golden Touch® Fast Flush every second or third oil change. **Ensure vehicle is at operating temperature before performing the Golden Touch Fast Flush service.**

- 1) Remove drain plug and completely drain old oil from engine. 2) Replace drain plug. 3) Remove old oil filter and replace with a new filter. 4) Add entire contents of this bottle through the crankcase oil fill opening. If the vehicle requires more than four (4) quarts of oil, top up with an OEM specified oil to the full mark. The engine must have a proper level of oil before the service can be performed. 5) Replace oil filler cap. 6) Start engine and idle for at least 5 minutes to enable Fast Flush to clean sludge, varnish and gum deposits from internal engine parts. 7) Shut off engine. 8) Remove drain plug and completely drain Fast Flush product from engine. 9) Remove oil filter and replace with another new oil filter. 10) Replace drain plug and remove oil filler cap from crankcase oil fill opening. 11) Add fresh engine oil to crankcase and replace oil filler cap. Always follow vehicle specifications so as to not overfill with oil. 12) Check oil level on engine oil dipstick. Used Golden Touch Fast Flush should be disposed of with used motor oil utilizing environmentally approved procedures.

**NOTE: NOT INTENDED FOR USE IN DIESEL OR ROTARY ENGINES.**